

Roma Carpet Underlay For Underfloor Heating

Suitable for Heavy Contract and Domestic Use

Recommended for Stairs

Recommended For Underfloor Heating With A Low 0.8 Tog Value



Top Surface	Stitch bonded crepe paper	
Bottom Surface	Flat sponge rubber	
Nominal Thickness	6.70 mm	
Nominal Roll Weight	31.0 Kg	68.3 lb
Weight Per Unit Area	3087 g/m ²	91 oz/yd ²
Roll Length	7.3 m	24.0 ft
Roll Width	1.37 m	54 in
Guarantee	Lifetime of the carpet (When used in recommended areas)	

Recommended Areas of Use

Areas of heavy wear including stairs

Used where a firm fitting is required

BS. 5808 : 1991 Test Results - British Standard for Carpet Underlays

End Use Classification	BS. 5808	HC/U
Work of Compression after 1000 impacts	BS. 4098	>90 J/m ²
Retention of Work of Compression	BS. 4098	>75 %
Loss in Thickness after Static Loading	BS. 4939	<5.00 %
Loss in Thickness after Dynamic Loading	BS. 4052	<5.00 %
Resistance to Cracking	BS. 5808 (A)	Pass

Other Relevant Tests

Thermal Resistance (TOG Rating)	BS. 4745	0.8 TOG
---------------------------------	----------	---------

Disclaimer

Whilst every effort is made to ensure its accuracy, the data on this sheet is meant for information purposes only. The typical properties listed are the result of extensive laboratory tests, but since Ball and Young has no control over the end use of each material, we cannot guarantee these results are obtained in practice. Users should conduct their own tests to determine the suitability of each material to its intended application.